



# PER PRINT REPLACEMENT CARTRIDGE

# NatureCare FRC and Mydoprint FRC PRINT REPLACEMENT CARTRIDGES

The Champion cartridge system contains Single Part Print Developer Replenisher and a new high stability two Part Bleach-Fix Replenisher in an easy-to-use cartridge. All you have to do is invert the cartridge and insert it into the chemical cartridge delivery system on any Fuji Frontier print minilab. As with other Champion Photochemistry single part products, FRC Print Replacement Cartridge utilises clear, clean, homogeneous, odorless Single Part RA-4 chemistry solutions.

- Easy-to-use Drop-in Replacement for Fuji CP48/CP49 Cartridges
- Reduced machine maintenance
- Less reprints
- Less downtime
- Can be used with all manufacturers' emulsions
- Released from Fuji shackles you can decide

# P1 NatureCare FRC & MYDOPRINT FRC Print Developer Replenisher

- Replenishment rate of 45 mls/m<sup>2</sup> at 38.5°C
- Single Part (SP) homogeneous, clear developer replenisher which is easy to use.
- Clean formulation significantly reduces 3 types of developer dirt:
- 1. Developer Creep (oxidized developer agent on crossover rollers/racks).
- 2. Tar-like suspended oxidized compounds in the developer solution that stick to rollers and racks.
- 3. Cement-like calcified salts, caused by local hard water and paper hardening agent, which fall to the bottom of the tank.
- Easy drop-in replacement on top of existing chemistry.
- FRC PRINT Developer Replenisher is a drop-in replacement for Fuji CP48/CP49 processing chemistry at the same times, temperatures and replenishment rates.
- Extended shelf life minimum 1 year from the date of manufacture in unopened container.

# P2 NatureCare FRC & MYDOPRINT FRC Bleach-Fix Replenisher

- Replenishment rate of 35 mls/m<sup>2</sup> at 38°C.
- High stability Two Part Bleach-Fix.
- Clean working.
- Easy drop in replacement on top of existing chemistry.

# P3 NatureCare FRC Rinse Tablets

• Self-Dissolving, easy to use.


PROCESS SPECIFICATIONS		ICATIONS	**recommended starting point		***depends upon on # of wash tanks used	
Machine	Step	Processing Stage	Processing Time (Sec)	Recommended Temp.	Replenishment Rate	Preparation of Working Solution (1L)
Frontier 340 (CP 48)	P1	FRC Print Developer Replenisher	25	45°C	45± mls/m²**	1) 80mlsStarter 2) 842mls Water 3) 78mls Developer Concentrate
	P2	FRC Print Bleach-Fix Replenisher	25	40°C	35± mls/m²**	<ol> <li>654mls Water</li> <li>173mls Part A Bleach-Fix Conc</li> <li>173mls Part B Bleach-Fix Conc</li> </ol>
	P3	NatureCare Rinse Tablet	25	40°C	215***± mls/m²**	One Tablet in 5L Water
Frontier 350 (CP 48)	P1	FRC Print Developer Replenisher	45	38.5°C	45± mls/m²**	1) 80mlsStarter 2) 842mls Water 3) 78mls Developer Concentrate
	P2	FRC Print Bleach-Fix Replenisher	45	38°C	35± mls/m²**	<ol> <li>654mls Water</li> <li>173mls Part A Bleach-Fix Conc</li> <li>173mls Part B Bleach-Fix Conc</li> </ol>
	P3	NatureCare Rinse Tablet	90	38°C	175***± mls/m²**	One Tablet in 5L Water
	P1	FRC Print Developer Replenisher	19	43°C	45± mls/m²**	1) 65mlsStarter 2) 857mls Water 3) 78mls Developer Concentrate
Frontier 570 (CP 49)	P2	FRC Print Bleach-Fix Replenisher	19	43°C	35± mls/m²**	<ol> <li>654mls Water</li> <li>173mls Part A Bleach-Fix Conc</li> <li>173mls Part B Bleach-Fix Conc</li> </ol>
	P3	NatureCare Rinse Tablet	19	45°C	175***± mls/m²**	One Tablet in 5L Water


#### CHEMISTRY SPECIFICATIONS

	P1 FRC Print De	veloper Replenisher	P2 FRC Bleach-Fix Replenisher		
	Seasoned Tank	Replenisher Tank	Seasoned Tank	Replenisher Tank	
рН	10.30 +/- 0.10	12.30 +/- 0.10	7.40 +/- 0.25	5.80 +/- 0.10	
SD (21.1°C) 1.057 +/- 0.010		1.035 +/- 0.010	1.115 +/- 0.010	1.126 +/- 0.010	

### FRC PRINT REPLACEMENT CARTRIDGE







For P3, NatureCare FRC Rinse Tablets, preparation of the working solution is the same as the Replenisher.

### STORAGE OF CHEMICALS:

#### Concentrates

All of the processing system concentrates have a normal storage life of at least 12 months, when held in unopened containers under steady temperature conditions 13°-18°C (56°F - 66°F). However, storage temperatures below 5°C (41.5°F) should be avoided as some crystallization may occur.

#### Working Solutions and Replenishers

Machine tank solutions should not be allowed to stand unused for more than one week, or the activity will be reduced by aerial oxidation. No more than one week's supply of any of the replenisher solutions should be made up at a time. Replenisher solutions should be kept covered with lids to reduce evaporation, oxidation and contamination.

#### Safe Use of Processing Chemicals

All chemicals should be kept out of reach of children. Refer to labels on the box and to the Material Safety Data Sheet for precautionary information. Protective clothing, including gloves and face/eye protection should always be worn when handling chemicals.

Contact our Service Plus Department or your local representative to determine which combination of chemicals is best suited for you.

#### **SUPPLIES**

	To make / To process	Product Code
<b>P1/P2</b> NatureCare FRC Print Replacement Cartridge	2x110m²	140183
P3 NatureCare FRC Rinse Table	ts 100x5L	140187
P1-S 47 Print Developer Starter	Variable	140407

**WARRANTY:** Seller, Champion Photochemistry Limited, expressly disclaims any and all warranties, express or implied, including any warranties of merchantability or fitness. Seller's sole obligation for defect is to replace the defective product. In no event shall seller have any liability for incidental or consequential damages.

Manufactured By \_

#### **CHAMPION PHOTOCHEMISTRY**

Lot 28-B Mukim Batu Industrial Area, 6½ Miles Jalan Kepong 52000 Kuala Lumpur, Malaysia Tel: (603) 6257-2600 Fax: (603) 6257-2622

Website: www.championphotochemistry.com

Fuji, Frontier and CP-48S are trademarks of Fuji Photo Film Co. Ltd