

**SECTION 1 - IDENTIFICATION OF CHEMICAL PRODUCT AND COMPANY**

Independent Photographic Supplies Pty Ltd  
PO Box 317  
Thornleigh, NSW 2120

Phone 02 9875 2244 Fax 02 9875 5448  
Mobile. 0407 221 835  
Email: technical@iphoto.com.au

**Substance:** Resin in a suitable solvent system.  
**Trade Name:** PremierArt Print Shield Bulk  
**Product Use:** Spray sealer for ink jet prints. Presented as a bulk liquid.  
**Creation Date:** September, 2009  
**This version issued:** September, 2009 and is valid for 5 years from this date.

**SECTION 2 - HAZARDS IDENTIFICATION****Statement of Hazardous Nature**

This product is classified as: Xn, Harmful. Xi, Irritating. F+, Highly Flammable. Hazardous according to the criteria of SWA.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R11, R36, R67. Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

**Safety Phrases:** S23, S26, S29, S33, S36, S24/25. Do not breathe vapours or mists. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. Do not empty into drains. Take precautionary measures against static discharges. Wear suitable protective clothing. Avoid contact with skin and eyes.

**SUSDP Classification:** None allocated.

**ADG Classification:** Class 3: Flammable liquids.

**UN Number:** 1263, PAINT RELATED MATERIAL

**Emergency Overview**

**Physical Description & colour:** Clear colourless mobile liquid.

**Odour:** Alcohol odour.

**Major Health Hazards:** No major health hazards. Product is an eye irritant, vapours may cause drowsiness and dizziness.

**Potential Health Effects****Inhalation:**

**Short term exposure:** Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term inhalation.

**Skin Contact:**

**Short term exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term skin exposure.

**Eye Contact:**

**Short term exposure:** This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**Long Term exposure:** No data for health effects associated with long term eye exposure.

**Ingestion:**

**Short term exposure:** Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term exposure:** No data for health effects associated with long term ingestion.

**Carcinogen Status:**

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**MATERIAL SAFETY DATA SHEET**

**IARC:** Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Isopropanol	67-63-0	>85	983	1230
n-Butyl acetate	123-86-4	<5	713	950
n-butanol	71-36-3	<3	152	Peak
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### SECTION 4 - FIRST AID MEASURES

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

**Inhalation:** No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

**Skin Contact:** Gently blot away excess liquid. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

### SECTION 5 - FIRE FIGHTING MEASURES

**Fire and Explosion Hazards:** This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

This product is likely to decompose only after heating to dryness, followed by further strong heating.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Suitable extinguishing media are carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** 12°C, Open cup

**Upper Flammability Limit:** 11.5% (IPA)

**Lower Flammability Limit:** 2.5%

**Autoignition temperature:** Does not burn.

**Flammability Class:** Flammable

## MATERIAL SAFETY DATA SHEET

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

## SECTION 7 - HANDLING AND STORAGE

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Isopropanol	983	1230
n-Butyl acetate	713	950
n-butanol	152	Peak

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: Viton, nitrile, butyl rubber, PE/EVAL, Responder.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

<b>Physical Description &amp; colour:</b>	Clear colourless mobile liquid.
<b>Odour:</b>	Alcohol odour.
<b>Boiling Point:</b>	Approx 82°C at 100kPa (IPA)
<b>Freezing/Melting Point:</b>	Below 0°C.
<b>Volatiles:</b>	Approx 90%
<b>Vapour Pressure:</b>	4.22 kPa at 20°C
<b>Vapour Density:</b>	2.1
<b>Specific Gravity:</b>	0.80
<b>Water Solubility:</b>	Slightly soluble.
<b>pH:</b>	No data.

### MATERIAL SAFETY DATA SHEET

<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	<1
<b>Coeff Oil/water distribution:</b>	No data
<b>Autoignition temp:</b>	Does not burn.

## SECTION 10 - STABILITY AND REACTIVITY

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully.

**Incompatibilities:** strong acids, strong bases, strong oxidising agents.

**Fire Decomposition:** This product is likely to decompose only after heating to dryness, followed by further strong heating. Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## SECTION 11 - TOXICOLOGICAL INFORMATION

**Toxicity:** IMMEDIATE (ACUTE) EFFECTS (Isopropanol):

Oral LD<sub>50</sub> (rat): 5045 mg/kg

Inhalation LC<sub>50</sub> (rat): 16,000 ppm/8 hours

Skin LD<sub>50</sub> (rabbit): 12,800 mg/kg

Skin Irritation (rabbit): 500 mg - mild

Eye Irritation (rabbit): 10 mg - moderate: 100 mg - severe

**DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:**

Subchronic Inhalation (rat): TCLo 5000 ppm/6 hr/day for 90 days (intermittent) caused a change in motor activity.

Chronic Inhalation (rat): TCLo 2500 ppm/6 hr/day for 2 years (intermittent) caused changes in liver and bladder weight and changes in urine composition.

**OTHER DATA:** Some very rare cases of skin hypersensitivity to Isopropanol have been reported. However, these cases do not at this time warrant Isopropanol to be classed as a sensitiser.

There is no data to hand indicating any particular target organs.

### Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Isopropanol	Conc>=20%: Xi; R36

## SECTION 12 - ECOLOGICAL INFORMATION

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

**Isopropanol:**

Biodegradation: 58% theoretical BOD, 5 days at 20°C - Relatively biodegradable.

Bioconcentration: Not expected to bioaccumulate in aquatic organisms based on low octanol/water partition coefficient.

Acute Toxicity (fathead minnow): LC<sub>50</sub> 10.4 g/L /96 hr.

**Daphnia:** EC<sub>50</sub> >1000mg/L

**Fish:** LC<sub>50</sub> fathead minnow (Pimephales promelas): 9600mg/L

## SECTION 13 - DISPOSAL CONSIDERATIONS

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## SECTION 14 - TRANSPORT INFORMATION

**ADG Code:** 1263, PAINT RELATED MATERIAL

**Hazchem Code:** 3YE

**Special Provisions:** 163

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

**Dangerous Goods Class:** Class 3: Flammable liquids.

**Packaging Group:** II

**Packaging Method:** P001, IBC02

## MATERIAL SAFETY DATA SHEET

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

### SECTION 15 - REGULATORY INFORMATION

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations.

### SECTION 16 - OTHER INFORMATION

**This MSDS contains only safety-related information. For other data see product literature.**

#### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons
<b>UN Number</b>	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2001(2003)]

Copyright © Kilford & Kilford Pty Ltd, September, 2009.

<http://www.kilford.com.au/> Phone (02)9251 4532

### MATERIAL SAFETY DATA SHEET