

Film for Mobile and Stationary Speeding Supervision and Red Light Supervision

Traffic Surveillance Colour Film: MACO TCS400

The special requirements of traffic supervision, like high sharpness for the registration of license plates, as well as very good fineness of grain for the identification of the car drivers, were taken into consideration with the concept of this film.

The MACO TCS400 owns a high exposure reserve for the application with difficult lighting conditions, and multi – lane driveways. The practical film speed sensitivity lies between ISO 400/27° and ISO 800/30°.

Characteristics:

- · Panchromatic colour negative film
- Wide latitude from +/- one f/stop, with high exposure reserve, for the application with all lighting Conditions and weather terms
- Special coating for the improvement of transport qualities in the cameras
- Use with daylight as well as with artificial light unconditionally possible
- · Acetate film base with high breaking strength and resistance of tearing
- The large contrast area guarantees the reproduction of the different tonality values
- Very good resolution power, very fine grain and very high sharpness, as a basis for negatives with an excellent quality
- Extra hard protective coating on both sides of the film for the avoidance of scratches
- Especially suitable for the digital evaluation over scanner

Technical Data

<u>Layer bearer:</u> dimension-containing, tear proof acetate base, 100µm, crystal clear

Layer construction:

- Emulsion side: protective coating + color emulsion + acetate base 100µm

- Back Side: NC-protective coating

 Total layer thickness:
 137,0μm

 Sensitivity:
 ISO 400/27°

 Grainess:
 RMS (x1000): 7.0

Resolution: contrast: 1000:1 Lp/mm: 130

<u>Darkroom lighting:</u>

The MACO TCS400 Film is to be processed within complete darkness.

Black shield effect

Exposure reading in seconds $^{1}/10000 - 1$ Exposure correction in seconds $^{N/A}$ Correction of the processing time $^{N/A}$

Exclusively Available in Australia & New Zealand from:

	INDEPENDENT PHOTOGRAPHIC SUPPLIES Pty Ltd		INDEPENDENT PHOTOGRAPHIC SUPPLIES NZ Limited			
	ABN: 36 105 600 351 P.O. Box 317, Thornleigh NSW 2120 Australia		Coy. # 1951487			
			P.O. Box 35840, Browns Bay, Auckland 0753 New Zealand			
	Ph: +61 2 9875 2244	Fax: +61 2 9875 5448	Ph - 1: +64 2 7485 7220	Ph – 2: +64 2 7472 2064		
	email: sales@iphoto.net.au	www.iphoto.net.au	email::sales@iphotonz.co.nz	www.iphotonz.co.nz		



Storage:

- Un-exposed film: up to 24 months, with cold storage of 8°C is recommended


- Exposed film: after exposure process film as soon as possible

DIAGRAM:

Typical Curve:

Sensitometric Characteristic Curves Exposure : Daylight 1/100 sec. Dansitometry : Status M 2.0 -3.00 -2.00 -1.00 0 +1.00 Log Exposure

Spectral Sensitivity:



Density curve:

Daylight 1/1000 s

Film process Color negative process C41

Processing:

The MACO TCS400 film is to be processed in the Colour Negative process C-41, or compatible process.

Catalogue Number/ Description

N-TCS400 Maco TCS Eagle Colour Film 400-30.5m \$P.O.A.

Exclusively Available in Australia & New Zealand from:

INDEPENDENT PHOTOGRAPHIC SUPPLIES Pty Ltd ABN: 36 105 600 351		INDEPENDENT PHOTOGRAPHIC SUPPLIES NZ Limited		
		Coy. # 1951487		
P.O. Box 317, Thornleig	P.O. Box 317, Thornleigh NSW 2120 Australia		P.O. Box 35840, Browns Bay, Auckland 0753 New Zealand	
Ph: +61 2 9875 2244	Fax: +61 2 9875 5448	Ph - 1: +64 2 7485 7220	Ph – 2: +64 2 7472 2064	
email: sales@iphoto.net.a	au <u>www</u> .iphoto.net.au	email:: sales@iphotonz.co.nz	www.iphotonz.co.nz	